

COAT BARRIER

DESCRIPTION

Coat Barrier is a water based liquid product specially formulated to leave a thin, temporary film on cargo hold surfaces. The film provides a barrier between the cargo and the cargo hold surfaces making the cleaning operation after unloading quicker and easier, and optimal cleaning result is achieved. Ec Coat is safe to the environment and to the personnel handling it, and will not contaminant the cargo. It is non-corrosive and safe on all coatings.

APPLICATIONS

After drying, creates a thin, non- sticky film on the cargo hold surfaces. The film substantially facilitates the cleaning before next cargo in two ways:

1. The film fills the minute pores in the surface, and prevents that small particles are trapped in the pores.
2. Small, solid particles can be very difficult to remove especially from organic coatings, even with the use of effective cleaning agents and high pressure water jets. The reason is the build-up of electromagnetic forces, and sometimes the only way to remove the particles is by scrubbing. Coat Barrier provides a barrier between the particles and the surface that minimize this problem, and the particles may now be removed with high pressure water only. The film is completely water soluble and is easy to remove even with cold sea water. To avoid re-deposition of contaminants a cleaning agent should be used, but at lower dosage rates than what normally is required. Coat Barrier may also be sprayed on deck, superstructure and other areas exposed to dust during loading and unloading operations.

COAT BARRIER

Water Based liquid specially for-mulated to leave a thin temporary film on cargo hold surfaces.

PRODUCT CHARACTERISTICS:

Colour: Colourless

Density: 1,00 - 1,01 g/cm³ at 20 deg C

pH : 9 at 100 % concentration

Solubility in water: 100%

Directions for Use and Dose Rates

The cargo hold surfaces should be as clean and dry as possible before treatment. Coat Barrier is supplied at ready to use concentration and may be applied directly from the drum. Spray the liquid on the cargo hold surfaces by the use of suitable low-pressure spraying equipment. As soon as the surface appears water wet, a proper film is created do not apply more than necessary. 1Ltr Coat Barrier will cover 15-20 m². Allow the film to dry completely before loading the cargo. Depending on air temperature and humidity this will take 1 to 2 hours. After reloading apply a 2-5% solution of a cleaning agent in water to avoid re-deposition of contaminants and finally flush with clean high pressure water.